

Please type a plus sign (+) inside this box → ☐

PTO/SE/05 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

46915 DIV

Total Pages

First Named Inventor or Application Identifier

MELDER et al.

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)

2. ☒ Specification [Total Pages 17]
(preferred arrangement set forth below)

- Descriptive title of the invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to Microfiche Appendix
- Background of the invention
- Brief Summary of the invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☐ Drawing(s) (35 USC 113) [Total Sheets ☐

4. Oath or Declaration [Total Pages 4]

- a. ☐ Newly executed (original or copy)
- b. ☒ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]

☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b)

5. ☒ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 4b,
is considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application,
Statement(s) ☐ Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☒ Divisional ☐ Continuation-in-part (CIP) of prior application No. 09 / 180,294

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

or ☐ Correspondence address below

(Insert Customer No. or Attach bar code label here)

NAME Herbert B. Keil

ADDRESS

KEIL & WEINKAUF
1101 Connecticut Avenue, N.W.
Washington, D.C. 20036

CITY

STATE

ZIP CODE

COUNTRY

USA

TELEPHONE

(202) 659-0100

FAX

(202) 659-0105

Burden hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

The filing fee has been calculated as shown below:

For:	Number Filed	Number Extra	Small/Large Entity	Basic Fee \$345/\$690
Basic Fee				\$ 690.00
Total Claims:	9	-20=	x \$9/\$18	=
Indep. Claims:	1	-3=	x \$39/\$78	=
[] Multiple Dependent Claim(s) presented: \$130/\$260				=
[] Non-English specification fee: \$130				=
[X] A check is enclosed for the filing fee.				\$ 690.00

[X] A check for \$ 690.00 for the above fees is enclosed.

[X] Authorization is hereby given to charge any deficiency in fees, including any extension fees, during the prosecution of this application and for the present filing, to Dep. Acct. 11-0345.

September 19, 2000

Date

HB Keil

Herbert B. Keil
Reg. No. 18,967

HBK/kas

1101 Connecticut Ave., N.W.
Washington, D.C. 20036
(202) 659-0100

001260" E0E9960

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of)
MELDER et al.)
Serial No. TO BE ASSIGNED)
Filed: WITH DIVISIONAL APPLICATION)
For: PREPARATION OF POLYALKENEAMINES)

Honorable Commissioner of
Patents and Trademarks
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Sir:

Prior to examination of the present divisional application, kindly amend the application as follows.

IN THE SPECIFICATION

Page 1, after the title, insert:


-- This is a Divisional Application of Serial No. 09/180,294, filed on November 5, 1998, which is a National Stage Application under 35 USC 371, based on International Application No. PCT/EP 97/02571, filed May 20, 1997.--

IN THE CLAIMS

Cancel claims 1-25.

Add new claims 26-34 as follows:


- 26. A polyalkene amine which is substantially free of halides and has the formula (I)



where

R_1 , R_2 , R_3 and R_4 , independently of one another, are each hydrogen or an unsubstituted or substituted, saturated or mono- or polyunsaturated aliphatic radical having a number-average molecular weight of up to 40000, at least one of the radicals R_1 to R_4 having a number average molecular weight of from 150 to 40000, and

R_5 and R_6 , independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl, hetaryl or an alkyleneimine radical of the formula (II)



where

Alk is a straight-chain or branched alkylene,

m is an integer from 0 to 10, and

R₇ and R₈, independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl or hetaryl or, together with the nitrogen atom to which they are bonded, form a heterocyclic structure,

or R₅ and R₆, together with the nitrogen atom to which they are bonded, form a heterocyclic structure, it being possible for each of the radicals R₅, R₆, R₇ and R₈ to be substituted by further alkyl radicals carrying hydroxyl or amino groups.

27. A polyalkene amine as defined in claim 26, of the general formula (IV), whose polyalkene portion is formed of C₂-C₄ alkene monomers.

28. A polyalkene amine as defined in claim 27, wherein the C₂-C₄ alkene is 1-butene or isobutene.

29. A polyalkene amine as defined in claim 26, which is derived from a reactive polyalkene with a high proportion of terminal double bonds.

30. A polyalkene amine as defined in claim 26, wherein the amine portion is derived from a nitrogen compound of formula (V).

31. A polyalkene amine as defined in claim 30, wherein the nitrogen compound is selected from ammonia, ethylene-1,2-diamine, propylene-1,2-diamine, propylene-1,3-diamine, butylene diamines, the mono-, di- and trialkyl derivatives of said

amines, polyalkylene polyamines, the alkylene portions of which do not have more than 6 carbon atoms, the N-amino-C₁-C₆-alkyl piperazine.

32. A polyalkylene amine as defined in claim 31, which is derived from a polyalkene epoxide of the general formula (IV), the polyalkene portion of which is formed of 1-butene or isobutene monomers and the amine portion of which is derived from ammonia.

33. A fuel composition containing at least a polyalkene amine defined in claim 26 in a concentration of about 20 to 5000 mg/kg of fuel as an additive for keeping the fuel intake system clean.

34. A lubricant composition containing as an additive at least one polyalkene amine as defined in claim 28 in a proportion of about 1 to 15% by weight, based on the total weight of the composition.--

REMARKS

Claims 26-34 are drawn to the nonelected invention, and the claims were canceled in parent application Serial No. 09/180,294, by examiner's amendment. An early examination on the merits is requested.

Favorable action is solicited.

Please charge any shortage in fees due in connection with the filing of this paper, including Extension of Time fees to Deposit Account No. 11-0345. Please credit

MELDER et al., DIV of SN 09/180,294

any excess fees to such deposit account.

Respectfully submitted,

KEIL & WEINKAUF



Ronald H. Smith
Reg. No. 43679

1101 Connecticut Ave., N.W.
Washington, D.C. 20036
(202)659-0100

RHS/kas

Preparation of polyalkeneamines

- 5 The present invention relates to a process for the preparation of polyalkeneamines from epoxides. The products prepared according to the invention are used in particular as fuel and lubricant additives.
- 10 Carburettors and intake systems of gasoline engines as well as injection systems for metering fuel in gasoline and diesel engines are increasingly being contaminated by impurities. The impurities are caused by dust particles from the air sucked in by
- 15 the engine, uncombusted hydrocarbon residues from the combustion chamber and the crankcase vent gases passed into the carburettor.
- These residues shift the air/fuel ratio during idling and in the lower part-load range so that the mixture becomes richer and the
- 20 combustion more incomplete. Consequently, the proportion of uncombusted or partially combusted hydrocarbons in the exhaust gas and the gasoline consumption increase.
- It is known that these disadvantages can be avoided by using fuel
- 25 additives for keeping valves and carburettor or injection systems clean (cf. for example M. Rossenbeck in Katalysatoren, Tenside, Mineralöladditive, Editors J. Falbe and U. Hasserodt, page 223, G. Thieme Verlag, Stuttgart 1978). Depending on the mode of action and preferred place of action of such detergent additives,
- 30 a distinction is now made between two generations. The first generation of additives was capable only of preventing the formation of deposits in the intake system but not of removing existing deposits. On the other hand, the additives of the second generation can prevent and eliminate deposits (keep-clean- and
- 35 clean-up effect). This is permitted in particular by their excellent heat stability in zones of relatively high temperature, in particular in the intake valves.
- 40 The molecular structural principle of these additives of the second generation which act as detergents is based on the linkage of polar structures to generally higher molecular weight, nonpolar or oleophilic radicals. Typical members of the second generation of additives are products based on polyisobutene in the nonpolar moiety, in particular additives of the
- 45 polyisobuteneamine type and of the polyisobutene amino alcohol

type. Such detergents can be prepared starting from polyisobutenes, by various multistage synthesis processes.

5 Polyisobuteneamino alcohols are prepared by first epoxidizing polyisobutenes and then reacting the epoxide with the desired amine. Such processes catalyzed by homogeneous or heterogeneous catalysts are described, for example, in WO 92/12221, WO 92/14806, EP 0 476 485 and EP 0 539 821.

10 Polyisobuteneamines are obtained starting from polyisobutene, essentially by two processes.

15 The first process involves chlorination of the polymeric parent structure followed by nucleophilic substitution by amines or preferably ammonia. The disadvantage of this process is the use of chlorine, which results in the occurrence of chlorine- or chloride-containing products, which is by no means desirable today and should if possible be avoided. For example, German
20 Laid-Open Applications DE-OS 2,129,461 and DE-OS 2,245,918 describe the reaction of halogen-containing hydrocarbons with an amine compound in the presence of a hydrogen halide acceptor.


In the second process, the polyisobuteneamines are prepared
25 starting from polyisobutene by hydroformylation and subsequent reductive amination. For example, EP 0 244 616 and German Patent 3,611,230 describe the carbonylation of polybutene or polyisobutene in the presence of a homogeneous catalyst, eg. cobalt octacarbonyl, and the subsequent conversion of the oxo
30 product into the amine. The disadvantages of this process are the high level of technical complexity of the carbonylation of the reactive polyisobutene under high pressure conditions and the special measures for removing the homogeneous carbonylation catalyst.

35

It is an object of the present invention to provide a process for the preparation of polyalkeneamines which is simpler to carry out than the processes known to date and gives an essentially
40 halide-free product. In particular, the novel process should be capable of being carried out starting from polyalkene without the complicated oxo synthesis.

We have found that this object is achieved by providing a process
45 for the preparation of polyalkeneamines of the formula (I)

3




5

where

10 R_1 , R_2 , R_3 and R_4 , independently of one another, are each hydrogen or an unsubstituted or substituted, saturated or mono- or polyunsaturated aliphatic radical having a number-average molecular weight of up to about 40000, at least one of the radicals R_1 to R_4 having a number average molecular weight of from about 150 to about 40000, and

15 R_5 and R_6 , independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl, hetaryl or an alkyleneimine radical of the formula (II)



20

where

25

Alk is straight-chain or branched alkylene,

m is an integer from 0 to 10, and

30

R_7 and R_8 , independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl or hetaryl or, together with the nitrogen atom to which they are bonded, form a heterocyclic structure,


or

35

R_5 and R_6 , together with the nitrogen atom to which they are bonded, form a heterocyclic structure, it being possible for each of the radicals R_5 , R_6 , R_7 and R_8 to be substituted by further alkyl radicals carrying hydroxyl or amino groups,

wherein an epoxide of the formula (IV)


40



45

4


where R_1 , R_2 , R_3 and R_4 have the abovementioned meanings, is reacted with a nitrogen compound of the formula (V)



5

where R_5 and R_6 have the abovementioned meanings, to give the amino alcohol of the formula (VI)

10



15

the amino alcohol of the formula (VI) is catalytically dehydrated and the olefin formed is hydrogenated to give the amine of the formula (I).

20

In a first preferred embodiment, the conversion of the epoxide (IV) to the amine (I) is carried out in one stage by reacting the epoxide (IV) with the nitrogen compound (V) in the presence of hydrogen and of a catalyst which has dehydrating and at the same time hydrogenating properties.

25

In a second preferred embodiment, the conversion of the epoxide (IV) to the amine (I) is carried out in two stages by first reacting the epoxide (IV) with the nitrogen compound (V) in the presence of an alkoxylation catalyst to give the amino alcohol (VI) and, if necessary, separating off unconverted reactants. The amino alcohol (VI) is hydrogenated in a second stage in the presence of a catalyst which has dehydrating and at the same time hydrogenating properties to give the amine (I).

35

The second process variant is advantageous in particular when reactants which are capable of undergoing undesirable secondary reactions under the chosen reaction conditions are used. This may be the case, for example, when ethylenediamine is used as the nitrogen compound of the formula (V). In the presence of the catalyst used according to the invention and having dehydrating and hydrogenating properties, dimerization with formation of piperazine may take place here, it being possible to avoid this if the amino alcohol (VI) is first produced in a first process stage, unconverted amine is removed and then, after the addition

45

of the catalyst, dehydration and hydrogenation are carried out to give the end product (I).

The catalyst which can be used according to the invention and
5 having dehydrating and hydrogenating properties is preferably
chosen from zeolites or porous oxides of Al, Si, Ti, Zr, Nb, Mg
and/or Zn, acidic ion exchangers and heteropolyacids, each of
which carries at least one hydrogenation metal. The hydrogenation
metals used are preferably Ni, Co, Cu, Fe, Pd, Pt, Ru, Rh or
10 combinations thereof.

Zeolites which may be used according to the invention are, for
example, solid acidic zeolite catalysts which are described in
15 EP 0 539 821, which is hereby incorporated by reference. Examples
of suitable zeolites are zeolites having the mordenite, chabasite
or faujasite structure, zeolites of the A, L, X and Y type,
zeolites of the pentasil type having an MFI structure, zeolites
in which some or all of the aluminum and/or silicon is replaced
20 by foreign atoms, eg. aluminosilicate, borosilicate,
ferrosilicate, beryllosilicate, gallosilicate, chromosilicate,
arsenosilicate, antimonosilicate and bismuthosilicate zeolites or
mixtures thereof and aluminogermanate, borogermanate,
gallogermanate and ferrogermanate zeolites or mixtures thereof or
25 titanium silicate zeolites, such as TS-1, ETS 4 and ETS 10.

To optimize the selectivity, conversion and lives, the zeolites
used according to the invention can be doped in a suitable manner
with further elements, as described, for example, in
30 EP 0 539 821.

Doping of the zeolites with the abovementioned hydrogenation
metals can be carried out in the same manner. The hydrogenation
metal should be present in an amount of from 1 to 10 % by weight,
35 based on the total weight of the catalytically active material
and calculated as oxide.

Further suitable catalysts having dehydrating and hydrogenating
properties are oxides, preferably acidic ones, of the elements
40 Al, Si, Zr, Nb, Mg or Zn or mixtures thereof, which are doped
with at least one of the abovementioned hydrogenation metals. The
oxide (calculated as Al_2O_3 , SiO_2 , ZrO_2 , Nb_2O_5 , MgO or ZnO) is
present in an amount of from about 10 to 99, preferably from
about 40 to 70, % by weight in the catalyst material (ie.
45 catalytically active material). The hydrogenation metal
(calculated as NiO , CoO , CuO , Fe_2O_3 , PdO , PtO , RuO_2 or Rh_2O_3) is
present in an amount of from about 1 to 90, preferably from about

30 to 60, % by weight, based on the total weight of the catalyst material. In addition, the oxides used according to the invention may contain small amounts, ie. from 0.1 to about 5 % by weight (calculated for the oxides) of further elements, such as Mo or Na, in order to improve catalyst properties, such as selectivity and life.


Oxides of this type and their preparation are described, for example, in EP 0 696 572, which is hereby incorporated by reference. The preparation is preferably carried out by preparing an aqueous salt solution which contains the abovementioned catalyst components and effecting coprecipitation by adding a mineral base, eg. sodium carbonate, with or without gentle heating. The precipitate is separated off, washed, dried and calcined, for example by heating for 4 hours at 500°C.

The novel zeolites and active oxides described above can, if required, be conditioned by milling them, if necessary, to a certain particle size and molding them to give extrudates or pellets, it being possible to add mold assistants, eg. graphite.

The use of a catalyst which contains, based on the total weight of the catalytically active material, about 30 % by weight of Zr, calculated as ZrO_2 , about 50 % by weight of Ni, calculated as NiO, about 18 % by weight of Cu, calculated as CuO, about 1.5 % by weight of Mo, calculated as MoO_3 and about 0.5 % by weight of Na, calculated as Na_2O is particularly preferred according to the invention.

Alkoxylation catalysts which are preferably added to the reaction mixture according to the invention promote the opening of the epoxide ring. Examples of suitable alkoxylation catalysts are water and alcohols, such as methanol and ethanol, mineral acids and carboxylic acids.

The polyalkene of the formula (III)



which is used as a starting material for the preparation of the epoxide of the formula (IV) is a polymer derived from at least one straight-chain or branched C₂-C₃₀-alkene, preferably C₂-C₆-alkene, in particular C₂-C₄-alkene, at least one of the radicals R₁ to R₄ having a number average molecular weight of from about 150 to 40000.

Examples of C₂-C₄-alkenes are ethylene, propylene and in particular 1-butene and isobutene.

The polyalkenes of the formula (III) which are preferably used according to the invention are reactive polyalkenes having a high proportion of terminal double bonds. A possible method for the preparation of reactive polyalkenes is described, for example, in German Laid-Open Application DE-OS 2,702,604.

Polyisobutene having a number average molecular weight of from about 800 to 1500 is particularly preferred.

Reactive polypropylenes may also be used according to the invention. These are obtained in particular by metallocene catalysis according to German Laid-Open Application DE-OS 4,205,932 and have terminal double bonds which are predominantly present as vinylidene groups. Vinyl-terminated polypropylenes are obtained, for example, according to EP 0 268 214.

The disclosure of the abovementioned patent applications is hereby incorporated by reference.

Preferred catalyst systems for the preparation of vinyl-terminated polymers are bis(pentamethylcyclopentadienyl)zirconium dichloride and bis(pentamethylcyclopentadienyl)hafnium dichloride in a solution of methylalumoxane in toluene.


Preferred catalysts for the preparation of vinylidene-terminated polymers are bis(n-butylcyclopentadienyl)zirconium dichloride, bis(octadecylcyclopentadienyl)zirconium dichloride and bis(tetrahydroindenyl)zirconium dichloride, in each case in a solution of methylalumoxane in toluene.

The polyalkenes of the formula (III) which are described above are first converted into the epoxide of the formula (IV). The epoxidation is carried out, for example, by dissolving the

polyalkene in a suitable solvent, eg. diethyl ether or another dipolar aprotic solvent or nonpolar solvent, such as xylene or toluene, drying this solution if necessary, adding the epoxidizing agent and carrying out epoxidation, if required with gentle heating, for example to about 40-70°C. Conventional epoxidizing agents are used for carrying out the epoxidation. Examples of these are peracids, such as peroxybenzoic acid, m-chloroperoxybenzoic acid and peroxyacetic acid, and alkyl peroxides, such as tert-butyl hydroperoxide, m-chloroperoxybenzoic acid and peroxyacetic acid being preferred.

In the epoxidation, epoxides of different stereoisomeric forms may be obtained individually or as a mixture, for example compounds of the general formulae (IVa), (IVb), (IVc) and (IVd)

15



A certain isomer can be used for the reaction with the nitrogen compound of the formula (V); usually, however, an isomer mixture is used for carrying out the amination.

Examples of suitable nitrogen compounds of the formula (V) are ammonia, ethylene-1,2-diamine, propylene-1,2-diamine, propylene-1,3-diamine, butylenediamines and the monoalkyl, dialkyl and trialkyl derivatives of these amines, eg. N,N-dimethylpropylene-1,3-diamine. Polyalkylenepolyamines whose alkylene radicals are of not more than 6 carbon atoms, for example polyethylenepolyamines, such as diethylenetriamine, triethylenetetramine and tetraethylenepentamine, and polypropylenepolyamines may also be used. Further examples are N-amino-C₁-C₆-alkylpiperazines. Ammonia is preferably used.

In both of the process variants described above, which can be carried out either continuously or batchwise, the epoxides are reacted with the nitrogen compound of the formula (V) at from about 80 to 250°C, preferably from about 150 to 210°C, and at hydrogen pressures of up to about 600, preferably from about 80

to 300, bar. The nitrogen compound is used in a molar ratio of from about 1:1 to about 40:1, preferably in an excess of from about 5:1 to about 20:1, based on the epoxide. The reaction may be carried out either in the absence of a solvent or in the presence of a solvent (for example hydrocarbons, such as hexane, or tetrahydrofuran).

The alkyl radicals present in the compounds of the formula (I) which are prepared according to the invention include in particular straight or branched, saturated carbon chains of 1 to 10 carbon atoms. Examples are lower alkyl, ie. C₁-C₆-alkyl, such as methyl, ethyl, n-propyl, isopropyl, n-butyl, sec-butyl, isobutyl, tert-butyl, n-pentyl, sec-pentyl, isopentyl, n-hexyl and 1-, 2- and 3-methylpentyl, longer-chain alkyl, such as straight-chain heptyl, octyl, nonyl and decyl, and the branched analogs thereof.

The compounds prepared according to the invention can, if required, contain hydroxyl and aminoalkyl radicals, in which the alkyl moiety is as defined above and the hydroxyl or amino group is preferably present on a terminal carbon atom.

The alkenyl radicals present in the compounds prepared according to the invention include in particular straight or branched carbon chains having at least one carbon-carbon double bond and 2 to 10 carbon atoms. Examples of monounsaturated C₂-C₁₀-alkenyl radicals are vinyl, allyl, 1-propenyl, isopropenyl, 1-, 2- and 3-butenyl, methallyl, 1,1-dimethylallyl, 1-, 2-, 3-, 4- and 5-hexenyl, longer-chain radicals, such as straight-chain heptenyl, octenyl, nonenyl and decenyl, and the branched analogs thereof, it being possible for the double bond to occur in any desired position. According to the invention, both the cis- and the trans-isomers of the above C₂-C₁₀-alkenyl radicals are included.

The alkynyl radicals present in the compounds prepared according to the invention include in particular straight or branched carbon chains having at least one carbon-carbon triple bond and 2 to 10 carbon atoms. Examples include ethynyl, 1- and 2-propynyl, 1-, 2- and 3-butyne and the corresponding alkynyl analogs of the abovementioned alkenyl radicals.

Examples of cycloalkyl groups which may be used according to the invention include in particular C₃-C₇-cycloalkyl radicals, such as cyclopropyl, cyclobutyl, cyclopentyl, cyclohexyl, cycloheptyl,

10

cyclopropylmethyl, cyclopropylethyl, cyclopropylpropyl, cyclobutylmethyl, cyclobutylethyl, cyclopentylethyl and the like.

5 Examples of aryl radicals which may be used according to the invention are phenyl and naphthyl.

10 Arylalkyl radicals which may be used according to the invention are in particular phenyl-C₁-C₁₀-alkyl and naphthyl-C₁-C₁₀-alkyl, and examples of suitable alkylaryl radicals are C₁-C₁₀-alkylphenyl and C₁-C₁₀-alkylnaphthyl, the C₁-C₁₀-alkyl moiety in each case being as defined above.

15 The cycloalkyl, aryl and arylalkyl groups present in the compounds prepared according to the invention may contain 1 or more, eg. 1 to 4, heteroatoms, such as O, S and N, preferred heteroatoms being oxygen and nitrogen. Examples of cyclic heteroalkyl radicals are tetrahydrofuranyl, piperidinyl, piperazinyl and morpholinyl. Examples of heteroaryl groups are 20 5- or 6-membered aromatic ring systems which comprise from 1 to 4 of the stated heteroatoms, eg. furyl, pyrrolyl, imidazolyl, pyrazolyl, oxazolyl, isoxazolyl, oxadiazolyl, tetrazolyl, pyridyl, pyrimidinyl, pyrazinyl, pyradizynyl, triazinyl, tetrazinyl and the like. Heterocyclic groups of the same type 25 having at least one nitrogen heteroatom may be formed from the radicals R₅ and R₆ in the above formula (I) together with the nitrogen atom to which they are bonded.

30 The straight-chain or branched alkylene radicals present in the compounds prepared according to the invention include straight-chain C₁-C₁₀-alkylene radicals, eg. ethylene, propylene, butylene, pentylene and hexylene, and branched C₁-C₁₀-alkylene radicals, eg. 1,1-dimethylethylene, 1,3-dimethylpropylene, 1-methyl-3-ethylpropylene, 2,3-dimethylbutylene, 35 1,3-dimethylbutylene, 1,1-dimethylbutylene, 1,2-dimethylpentylene and 1,3-dimethylhexylene.

40 Examples of substituents which are suitable according to the invention are C₁-C₆-alkyl, amino-C₁-C₆-alkyl, hydroxy-C₁-C₆-alkenyl, C₁-C₆-alkyloxy, C₂-C₆-alkenyl, C₁-C₆-alkanoyl, eg. acetyl and propionyl, nitro and amino.

45 The polyalkeneamines of the formula (I) which are prepared according to the invention can be used as additives for liquid or pasty lubricant compositions. At least one of the novel polyalkeneamines is contained therein, if required in combination with further conventional lubricant additives. Examples of

11

conventional additives are corrosion inhibitors, antiabrasion additives, viscosity improvers, detergents, antioxidants, antifoams, lubricity improvers and pour point improvers. The novel compounds are usually contained in amounts of from about 1
5 to 15, preferably from about 0.5 to 10, in particular from 1 to 5, % by weight, based on the total weight of the composition.

Examples of such lubricants include oils and greases for motor vehicles and industrially used drive units, in particular engine
10 oils, gear oils and turbine oils.

The compounds prepared according to the invention may furthermore be contained as an additive in fuel compositions, for example in fuels for gasoline and diesel engines. The novel compounds serve
15 therein in particular as detergents for keeping the fuel intake system clean. Owing to their dispersing properties, they have an advantageous effect on the engine lubricant, which they may enter during operation. The polyalkeneamines prepared according to the
20 invention are metered into commercial fuels in concentrations of from about 20 to 5000, preferably from about 50 to 1000, mg/kg of fuel. The novel additives can, if required, also be added together with other known additives.

Whereas novel additives which have a number average molecular weight of from about 2000 to 40000 are preferably used in lubricant compositions, compounds having a number average
25 molecular weight of from about 150 to 5000, preferably from about 500 to 2500, in particular from about 800 to 1500, are particularly suitable for use as fuel additives.
30

Finally, compounds prepared according to the invention may also be present in combination with other additives, in particular detergents and dispersants. A combination with, for example,
35 polyisobutylamines disclosed in U.S. Patent 4,832,702 is particularly preferred.

Testing of the novel products as fuel additives, particularly with regard to their suitability as valve and carburettor
40 cleaners, is carried out with the aid of engine tests which are performed on the test bench with a 1.2 l Opel Kadett engine according to CEC-F-04-A-87.

A spot test, as described, for example, by A. Schilling in "Les
45 Huiles pour Moteurs et la Graissage des Moteur", Vol. 1, 1962, page 89 et seq., in slightly modified form, may be used for

12

testing the novel products with regard to their dispersant properties.

The Examples which follow illustrate the invention.

5

Examples

- 10 A 50 % strength solution of polyisobutene epoxide in Mihagol, which was prepared by epoxidation of Glissopal®1000 (commercial product from BASF AG), was used as a starting material in the examples below. The characterization of the aminoalkanes and of the corresponding amino alcohols was effected by determining
- 15 amine numbers and hydroxyl numbers.

- The catalyst used in the Examples below and having dehydrating and hydrogenating properties was prepared according to EP 0 696 572 and had the following composition (based in each
- 20 case on the total weight of the catalytically active material):
- 30 % by weight of ZrO_2
 - 50 % by weight of NiO
 - 18 % by weight of CuO
- 25 1.5 % by weight of MoO_3
- 0.5 % by weight of Na_2O

Example 1: One-stage, continuous reaction with ammonia

- 30 125 ml/hour of a 50 % strength solution of polyisobutene epoxide in Mihagol are reacted continuously with 250 ml/hour of ammonia in a 1 l tubular reactor filled with 500 g of catalyst. The reaction temperature in the reactor is from 200 to 205°C. The
- 35 pressure is 250 bar and the amount of hydrogen is 100 l/hour. The readily volatile components (water, ammonia and Mihagol) are distilled off under reduced pressure (up to a bottom temperature of 70°C at 3 mbar). The amine number of the product obtained is 30.0 and the hydroxyl number is 2.0.

40

Example 2: One-stage, batchwise reaction with ammonia

- 100 g of catalyst are added to 225 g of polyisobutene epoxide, dissolved in 225 g of Mihagol and 5 g of water. In the autoclave,
- 45 the mixture is heated at 200°C for 4 hours at a hydrogen pressure of 200 bar after the addition of 450 ml of ammonia. After all low boilers have been separated off under reduced pressure, a

13

solvent-free product having an amine number of 29.2 and a hydroxyl number of 4 is obtained, ie. the aminoalcohol was dehydrated and hydrogenated.

5 Example 3: Two-stage, batchwise reaction with ammonia

200 g of polyisobutene epoxide are dissolved in a mixture of 200 g of Mihagol, 300 ml of tetrahydrofuran and 12 g of water. In the autoclave, the mixture is heated at 200°C for 12 hours at a nitrogen pressure of 200 bar after the addition of 300 ml of ammonia. The readily volatile components (water, tetrahydrofuran, Mihagol) are distilled off under reduced pressure. The amine number of the product is 32.8 and the hydroxyl number is 32.2, ie. the desired amino alcohol is present.

100 g of the amino alcohol are dissolved in 400 g of Mihagol, and 100 g of catalyst are added. In the autoclave, the mixture is heated at 200°C for 24 hours at a hydrogen pressure of 200 bar after the addition of 500 ml of ammonia. After all low boilers have been separated off under reduced pressure, a solvent-free product having an amine number of 29 and a hydroxyl number of 2 is obtained, ie. the amino alcohol was dehydrated and hydrogenated.

25 58/Hg

30


35

40

45

We claim:


1. A process for the preparation of polyalkeneamines of the formula (I)



where

R_1 , R_2 , R_3 and R_4 , independently of one another, are each hydrogen or an unsubstituted or substituted, saturated or mono- or polyunsaturated aliphatic radical having a number-average molecular weight of up to about 40000, at least one of the radicals R_1 to R_4 having a number average molecular weight of from about 150 to about 40000, and

R_5 and R_6 , independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl, hetaryl or an alkyleneimine radical of the formula (II)



where

Alk is straight-chain or branched alkylene,

m is an integer from 0 to 10, and

R_7 and R_8 , independently of one another, are each hydrogen, alkyl, cycloalkyl, hydroxyalkyl, aminoalkyl, alkenyl, alkynyl, aryl, arylalkyl, alkylaryl or hetaryl or, together with the nitrogen atom to which they are bonded, form a heterocyclic structure,


or R_5 and R_6 , together with the nitrogen atom to which they are bonded, form a heterocyclic structure, it being possible for each of the radicals R_5 , R_6 , R_7 and R_8 to be substituted by further alkyl radicals carrying hydroxyl or amino groups,

wherein

2


an epoxide of the formula (IV)

5



10


where R_1 , R_2 , R_3 and R_4 have the abovementioned meanings, is reacted with a nitrogen compound of the formula (V)



15

where R_5 and R_6 have the abovementioned meanings, to give the amino alcohol of the formula (VI)

20



25

the amino alcohol of the formula (VI) is catalytically dehydrated and the olefin formed is hydrogenated to give the amine of the formula (I).

30

2. A process as claimed in claim 1, wherein the epoxide of the formula (IV) is reacted with the nitrogen compound of the formula (V) in the presence of hydrogen and of a catalyst which has dehydrating and at the same time hydrogenating properties.

35

3. A process as claimed in claim 1, wherein the epoxide of the formula (IV) is first reacted with the nitrogen compound of the formula (V) in the presence of an alkoxylation catalyst to give the amino alcohol of the formula (VI) and, if required, unconverted reactants are separated off, and the amino alcohol (VI) is then hydrogenated in the presence of a catalyst which has dehydrating and at the same time hydrogenating properties.

40

4. A process as claimed in claim 2 or 3, wherein the catalyst having dehydrating and hydrogenating properties is selected from zeolites or porous oxides of Al, Si, Ti, Zr, Nb, Mg or

45

3

Zn, acidic ion exchangers and heteropolyacids, each of which carries at least one hydrogenation metal.


- 5 5. A process as claimed in claim 4, wherein the hydrogenation metal is selected from Ni, Co, Cu, Fe, Pd, Pt, Ru, Rh and combinations thereof.
- 10 6. A process as claimed in claim 5, wherein the catalyst (catalytically active material) contains about 30 % by weight, calculated as ZrO_2 , of a zirconium compound, about 50 % by weight, calculated as NiO , of a nickel compound and about 18 % by weight, calculated as CuO , of a copper compound.
- 15 7. A process as claimed in any of the preceding claims, wherein the nitrogen compound and epoxide are used in a molar ratio of from about 1:1 to about 40:1.
- 20 8. A process as claimed in any of the preceding claims, wherein the reaction temperature is from about 80 to 250°C.
- 25 9. A process as claimed in any of the preceding claims, wherein a hydrogen pressure of up to about 600 bar is established.
- 30 10. A process as claimed in any of the preceding claims, wherein an epoxide of the formula (IV), where one of the radicals R_1 to R_4 has a number average molecular weight of from about 150 to 40000, is used.
- 35 11. A process as claimed in claim 10, wherein the epoxide is derived from a polyalkene which is a homo- or copolymer of C_2 - C_{30} -alkenes.
- 40 12. A process as claimed in claim 11, wherein the polyalkene is derived from at least one 1-alkene, selected from ethylene, propylene, 1-butene and isobutene.
- 45 13. A process as claimed in any of the preceding claims, wherein the nitrogen compound of the formula (V) is selected from NH_3 , monoalkylamines, dialkylamines and alkylenediamines having at least one primary or secondary amino group.

58/Hg

M/37044

Abstract

5 Polyalkeneamines of the formula (I)



10

where R_1 , R_2 , R_3 , R_4 , R_5 and R_6 may have different meanings, are prepared by a process in which a polyalkene epoxide is reacted with an amine and the amino alcohol is dehydrated and reduced to
15 give the compound of the formula (I).

20

25

58/Hg

30

35

40

45

(11)

Declaration, Power of Attorney

Page 1 of 4

O. Z. 0050/46915

We (I), the undersigned inventor(s), hereby declare(s) that:

My residence, post office address and citizenship are as stated below next to my name,

We (I) believe that we are (I am) the original, first, and joint (sole) inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Preparation of polyalkeneamines

the specification of which

☒ is attached hereto.

☐ was filed on _____ as

Application Serial No. _____

and amended on _____.

☒ was filed as PCT international application

Number _____

on _____

and was amended under PCT Article 19

on _____ (if applicable).

We (I) hereby state that we (I) have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

We (I) acknowledge the duty to disclose information known to be material to the patentability of this application as defined in Section 1.56 of Title 37 Code of Federal Regulations.

We (I) hereby claim foreign priority benefits under 35 U.S.C. § 119(a)–(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed. Prior Foreign Application(s)

Application No.	Country	Day/Month/Year	Priority Claimed
19620262.0	Federal Republic of Germany	20th May 1996	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

O. Z. 0050/46915

We (I) hereby claim the benefit under Title 35, United States Codes, § 119(e) of any United States provisional application(s) listed below.

 (Application Number)

 (Filing Date)

 (Application Number)

 (Filing Date)

We (I) hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Application Serial No.

Filing Date

Status (pending, patented,
abandoned)

<hr/>	<hr/>	<hr/>
<hr/>	<hr/>	<hr/>
<hr/>	<hr/>	<hr/>
<hr/>	<hr/>	<hr/>


And we (I) hereby appoint Messrs. **HERBERT. B. KEIL**, Registration Number 18,967; and **RUSSEL E. WEINKAUF**, Registration Number 18,495; the address of both being Messrs. Keil & Weinkauf, 1101 Connecticut Ave., N.W., Washington, D.C. 20036 (telephone 202-659-0100), our attorneys, with full power of substitution and revocation, to prosecute this application, to make alterations and amendments therein, to sign the drawings, to receive the patent, and to transact all business in the Patent Office connected therewith.

We (I) declare that all statements made herein of our (my) own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

O. Z. 0050/46915

Johann-Peter Melder

NAME OF FIRST OR SOLE INVENTOR


Signature of Inventor

Date

13th June 1997

Residence: *Jahnstr.35*

67141 Neuhofen


Federal Republic of Germany

Citizen of: *Germany*

Post Office Address: *same as residence*

Gerhard Blum

NAME OF SECOND JOINT INVENTOR


Signature of Inventor

Date

13th June 1997

Residence: *Sieglestr.29a*

67117 Limburgerhof


Federal Republic of Germany

Citizen of: *Germany*

Post Office Address: *same as residence*

Wolfgang Günther

NAME OF THIRD JOINT INVENTOR


Signature of Inventor

Date

13th June 1997

Residence: *Hauptstr.9*

67582 Mettenheim


Federal Republic of Germany

Citizen of: *Germany*

Post Office Address: *same as residence*

Dietmar Posselt

NAME OF FOURTH JOINT INVENTOR


Signature of Inventor

Date

13th June 1997

Residence: *Ziegelhäuser Landstr.7*

69120 Heidelberg

Federal Republic of Germany

Citizen of: *Germany*

Post Office Address: *same as residence*

Declaration

Page 4 of 4

O. Z. 0050/46915

Knut Oppenländer

NAME OF FIFTH JOINT INVENTOR

Residence: *Otto-Dill-Str. 23*

67061 Ludwigshafen

Federal Republic of Germany

Knut Oppenländer

Signature of Inventor

Citizen of: *Germany*

Post Office Address: *same as residence*

Date

13th June 1997

00T250" 09E99960